

DYROS 10

Brass connectors with 6 mm passage capacity* for water, grease, air, oil etc.

- developed specifically for coolants in plastic tools




Today Dyros 10 can be found everywhere:


- on plastic moulds
- on compressed-air plants
- on oxygen and gas cylinders
- in operating rooms
- and in numerous other places




In short, Dyros can be found wherever small dimensions, reliability and safety are a must.

All connectors have built-in valves that are perfectly tight even at very low pressure.

A locking device is automatically released upon engagement, so that the connector can be operated by one hand.

Safety connectors with hose fitting		3/8" (9,5 ^o)	1/2" (12,7 ^o)			
Straight					Art. No. SLK 16	Art. No. SLK 18
					Art. No. SVK 16/90	Art. No. SVK 18/90
					Art. No. SVK 16/45	

Safety connectors with internal thread		BSP1/4"	BSP3/8"	M14x1.5		
Straight		Art. No. SLKR 114 (HEX = 18)	Art. No. SLKR 138 (HEX = 20)		Art. No. SLKM 145 (HEX = 18)	

Safety connectors with external thread		BSP1/4"	BSP3/8"	M14x1.5		
Straight		Art. No. SLKUR 114 (HEX = 18)	Art. No. SLKUR 138 (HEX = 18)		Art. No. SLKUM 145 (HEX = 18)	
		Art. No. SVKUR 114/90	Art. No. SVKUR 138/90		Art. No. SVKUM 145/90	
		Art. No. SVKUR 114/45	Art. No. SVKUR 138/45		Art. No. SVKUM 145/45	

Dyros products are unimpeachable quality - down to the smallest detail

The Thread BSP corresponds to G1/4" - G3/8".

The connectors on these pages are also made without valve (OV).

All connectors can also be delivered with coloured red and blue caps.

Order e.g. with valve no. SLK 16
Without valve order no. SLK 16OV

Order e.g. valve no. SLK 16R = red cap

